

Japanese Kokai Patent Application No. Hei 2[1990]-302300
[Claims only, as requested]

JP 02-302300

Job No.: 6519-91726

Translated from Japanese by the Ralph McElroy Translation Company
910 West Avenue, Austin, Texas 78701 USA

JAPANESE PATENT OFFICE
PATENT JOURNAL (A)
KOKAI PATENT APPLICATION NO. HEI 2[1990]-302300

Int. Cl. ⁵ :	D 06 F 58/04
Sequence No. for Office Use:	6681-4L
Filing No.:	Hei 1[1989]-122363
Filing Date:	May 16, 1989
Publication Date:	December 14, 1990
No. of Claims:	2 (Total of 5 pages)
Examination Request:	Not filed

CLOTHES DRIER

Inventors:	Tatsuya Hirota Sanyo Electric Co. Ltd. 2-18 Keihanhondori, Moriguchi-shi, Osaka-fu
	Yoshiaki Aoki Sanyo Electric Co. Ltd. 2-18 Keihanhondori, Moriguchi-shi, Osaka-fu
	Koichi Tanaka Sanyo Electric Co. Ltd. 2-18 Keihanhondori, Moriguchi-shi, Osaka-fu
	Yozo Kawamura Sanyo Electric Co. Ltd. 2-18 Keihanhondori, Moriguchi-shi, Osaka-fu
Applicant:	Sanyo Electric Co. Ltd. 2-18 Keihanhondori, Moriguchi-shi, Osaka-fu

Agents:

Takushi Nishino, patent attorney,
and 2 others

[There are no amendments to this patent.]

Claims

1. A type of clothes drier characterized by the fact that it has the following means: a drying chamber for accommodating clothes; a drying means that feeds a flow of drying air into said drying chamber; a spray-type container that sprays a liquid finishing agent; a container installation part that enables installation, in a quick-connecting/disconnecting way, of said spray-type container for introducing said sprayed finishing agent into said drying chamber; and a manipulating means that manipulates said installed spray-type container in order to introduce the finishing agent.

2. A type of clothes drier characterized by the fact that it has the following means: a drying chamber for accommodating clothes; a drying means that feeds a flow of drying air into said drying chamber; a container that holds a liquid finishing agent; a connecting port that connects said container and said drying chamber; and a rotating body that is partially dipped in the finishing agent while rotating so as to spray said finishing agent through said connecting port into said drying chamber.

THIS PAGE BLANK (USPTO)